

## GETT® 100 KEYS TRACKBALL



GA-100F1-TB-USB-US (FRONT)



GA-100R1-TB-USB-US (REAR)

### SPECIAL FEATURES

- Water, dust and vandal resistant
- Etching and inking lettering
- Brushed surface
- Compatible with WINDOWS98/ME/2000/XP
- Can be cleaned with soapy water, disinfectant or other cleaning agents
- Designed for public, outdoor, industrial and other extreme surroundings

### SPECIFICATION

| Model No.              | GA-100R1-TB-USB-US        | GA-100R1-TB-USB-US-LED | GA-100F1-TB-USB-US | GA-100F1-TB-USB-US-LED |
|------------------------|---------------------------|------------------------|--------------------|------------------------|
| Mounting               | rear                      |                        | front              |                        |
| Backlight              | absent                    | present                | absent             | present                |
| Contact technology     | carbon on gold            |                        |                    |                        |
| Connectivity           | USB or PS/2               |                        |                    |                        |
| Number of keys         | 106 keys                  |                        |                    |                        |
| Key stroke travel      | 1.5mm                     |                        |                    |                        |
| Switching cycles       | approx. 1 mill. (per key) |                        |                    |                        |
| Protection level       | IP65                      |                        |                    |                        |
| Impact protection rate | IK07                      |                        |                    |                        |
| Housing colour         | stainless steel           |                        |                    |                        |
| Operating temperature  | -10°C ~ +45°C             |                        |                    |                        |
| Storage temperature    | -20°C ~ + 70°C            |                        |                    |                        |
| Relative humidity      | 30% to 95%                |                        |                    |                        |
| Atmospheric pressure   | 50kPa to 110kPa           |                        |                    |                        |
| Key actuation force    | 120g/1.18N                |                        |                    |                        |
| Power input            | +5V/DC, 10mA              |                        |                    |                        |
| Warranty               | 1 year                    |                        |                    |                        |
| Dimensions (mm)        | 478 x 135                 |                        | customized         |                        |
| Net Weight (kg)        | 2.1                       |                        |                    |                        |
| Gross Weight (kg)      | 2.5                       |                        |                    |                        |
| Certification          | EMC, FCC, CE              |                        |                    |                        |

Other layouts and configurations on request.