

GETT® 86 KEYS BASIC



GA-80F1-ST-USB-US (FRONT)



GA-80R1-ST-USB-US (REAR)

SPECIAL FEATURES

- Water, dust and vandal resistant
- Etching and inking lettering
- Brushed surface
- Compatible with WINDOWS98/ME/2000/XP
- Can be cleaned with soapy water, disinfectant or other cleaning agents
- Designed for public, outdoor, industrial and other extreme surroundings

SPECIFICATION

Model No.	GA-80R1-ST-USB-US	GA-80R1-ST-USB-US-LED	GA-80F1-ST-USB-US	GA-80F1-ST-USB-US-LED
Mounting	rear		front	
Backlight	absent	present	absent	present
Contact technology	carbon on gold			
Connectivity	USB or PS/2			
Number of keys	86 keys			
Key stroke travel	1.5mm			
Switching cycles	approx. 1 mill. (per key)			
Protection level	IP65			
Impact protection rate	IK07			
Housing colour	stainless steel			
Operating temperature	-10°C ~ +50°C			
Storage temperature	-20°C ~ + 70°C			
Relative humidity	30% to 95%			
Atmospheric pressure	50kPa to 110kPa			
Key actuation force	120g/1.18N			
Power input	+5V/DC, 10mA			
Warranty	1 year			
Dimensions (mm)	319 x 135		customized	
Net Weight (kg)	1.5			
Gross Weight (kg)	1.8			
Certification	EMC, FCC, CE			

Other layouts and configurations on request.